

**Spaces are included in the max character limits. Character limits will be enforced strictly!  
Do not include images in this document. Attach images in the online abstract submission form.  
Please see the following page for an example of a published abstract.**

**Full Name of Abstract Author**

**Email Address**

**General Details**

- Title (max 150 characters)
- Names
- Sponsorship

**Photo of Person**

- You will prompted to upload the headshot as part of the abstract submission process. **Do not include an image in this document.** Please follow the naming convention and list the file name below.
- Allowed File Types: JPG, TIFF
- Minimum requirements: 72 DPI resolution, 1600 pixels wide
- Aspect Ratio: 1:1 – a square photo
- Filename Convention: “*marc2026\_headshot\_kerberos*” (ex. *marc2026\_headshot\_jjpatil.jpg*)

**Abstract - With Image: max 1000 characters, Without Image: max 2000 characters**

**Abstract Image (Submitting an image is not mandatory)**

- Minimum requirements: 72 DPI resolution, 1600 pixels wide
- Allowed File Types: JPG, TIFF
- Aspect Ratio: Landscape images are preferred
- You will prompted to upload the abstract image as part of the abstract submission process. **Do not include an image in this document.** Please follow the naming convention and list the file name below.
- Filename Convention: “*marc2026\_image\_kerberos*” (ex. *marc2026\_image\_jjpatil.jpg*)
- Image Caption (max 250 characters)

**SAMPLE ABSTRACT SUBMISSION ON NEXT PAGE**

Jelena Notaros  
notaros@mit.edu

CMOS-Compatible Optical Phased Arrays Powered by Monolithically-Integrated Erbium Lasers  
J. Notaros, N. Li, C. V. Poulton, Z. Su, M. J. Byrd, E. S. Magden, E. Timurdogan, C. Baiocco, N. M. Fahrenkopf, and M. R. Watts

**Sponsorship:** DARPA E-PHI program (HR0011-12-2-0007) and NSF Graduate Research Fellowship (1122374)

Integrated optical phased arrays (OPAs), fabricated in advanced silicon photonics (SiP) platforms, enable dynamic high-speed control of free-space light. As such, OPAs have many promising wide-reaching applications, including light detection and ranging (LIDAR), holographic displays, and free-space communications. However, due to the absence of a direct-band-gap material in standard SiP platforms, many of these demonstrations have been limited to systems with fiber-coupled off-chip lasers, which restrict the practicality of the system due to packaging and cost concerns.

In this work, an erbium-doped laser and an electrically-steerable OPA are monolithically integrated in a CMOS-compatible 300-mm-wafer SiP platform. This system represents the first demonstration of an active CMOS-compatible SOI photonics system powered by a rare-earth-doped monolithically-integrated laser and paves the way for future monolithic SiP systems, such as data communication links and optical synthesizers.

(a) Simplified schematic (not to scale) and (b) photograph of the integrated optical phased array system powered by a monolithically-integrated erbium laser.